

CERTIFICATE OF COMPLIANCE

Certificate Number 20120921-E256366
Report Reference E256366-20050907
Issue Date 2012-SEPTEMBER-21

Issued to: CMP PRODUCTS
GLASSHOUSE ST, ST PETERS, NEWCASTLE-UPON-
TYNE, NE6 1BS UNITED KINGDOM

**This is to certify that
representative samples of**

CABLE FITTINGS FOR USE IN ZONE CLASSIFIED
HAZARDOUS LOCATIONS

See next page for models

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.


Standard(s) for Safety:

UL 2225, Standard for Metal-Clad Cable and Cable Sealing
Fittings for use in Hazardous (Classified) Locations,
UL 514B, Standard for Fittings for Cable and Conduit,
UL 60079-0, Electrical apparatus for explosive gas
atmospheres – Part 0: General Requirements,
UL 60079-7, Electrical apparatus for explosive gas
atmospheres – Part 7: Increased Safety “e”.

Additional Information:

See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Listing and Classification Marks should be considered as being covered by UL's Listing, Classification and Follow-Up Service.

The combined UL Listing and Classification Marks generally include the symbol UL in a circle:  with the word “LISTED”; a control number (may be alphanumeric) assigned by UL; and the product category name (product identifier) as indicated in the appropriate UL Directory and a statement “ALSO CLASSIFIED TO (extent of UL’s evaluation of the product)”.

Look for the UL Listing and Classification Mark on the product.



William R. Carney, Director, North American Certification Programs
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus



CERTIFICATE OF COMPLIANCE

Certificate Number 20120921-E256366
Report Reference E256366-20050907
Issue Date 2012-SEPTEMBER-21

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Series MCRA and TMC metal-clad cable connectors. For use in Class I, Zone 1, AEx e II hazardous areas when used with type MC-HL cable employing continuous corrugated aluminum cable. Conduit entry sizes ½ in. to 4 in. and M20 to M115 inclusive.

Series MCRA and TMC metal-clad cable connectors. For use in Class I, Zone 2, AEx e II hazardous areas when used with type MC cable employing interlocking aluminum armor cable, or interlocking steel armor cable. Conduit entry sizes ½ in. to 4 in. and M20 to M115 inclusive.



William R. Carney, Director, North American Certification Programs
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus

