

# CLF2-NW

## MV Heavy Duty Copper Compression Cable Lug - Flared Entry Long Barrel with 2 Stud Holes - Narrow Palm - Inspection Window

These flared entry products have been designed and third party certified to UL 486A-486B and CSA C22.2 No. 65, for high quality and reliable crimping.

Long barrel compression cable lugs enable additional crimps, offering increased electrical and mechanical properties.

Narrow palm cable lugs have a contained palm width to ensure a connection can be made in space constrained installations.

Manufactured from high purity, oxygen-free, seamless copper tube (C110/CW009A), these cable lugs are precisely dimensioned to achieve optimal crimping with suitable conductors.

The lugs are annealed to enhance durability, minimising risk of fracture between the palm and barrel. The tin coating ensures corrosion and oxidation resistance, ensuring maximum efficiency of the connection.

There is a large inspection window to visually inspect conductor insertion; the inspection window can be removed as an option - see data sheet CLF2-N.

The centres of the two stud holes are detailed in the dimensional table. Custom stud hole dimensions are available on request.



| TECHNICAL DATA & CLASSIFICATION |                          |
|---------------------------------|--------------------------|
| ETIM Classification Code        | EC001051                 |
| Barrel Type                     | Long                     |
| Entry Type                      | Flared                   |
| Lug Material                    | Tin Plated Copper        |
| Number of Stud Holes            | 2                        |
| Palm Angle                      | Straight                 |
| Temperature Rating              | Up to 90 Degrees Celsius |



## FEATURES

- Sizes to suit cables 4 AWG up to 1,000 kcmil
- Narrow palm width for space constrained connections
- Third Party Certified to UL 486A-486B and CSA C22.2 No. 65
- Manufactured from high purity (99.9%) copper seamless tube (BS EN 13600)
- Annealed and electrolytically tin plated for reliable crimping, with oxidation and corrosion resistance
- Colour coded with enhanced marking on the barrel for simple die selection, inspection and traceability
- CMP crimping die available for optimal crimping
- Flared entry to barrel for ease of conductor insertion; beneficial for class 5 and 6 conductors
- Sold in bags; product must be ordered in bag multiples. See table on following page for bag quantities
- Crimping die index numbers match wire size; refer to CMP compatible die chart for more information





| LUG IDENTIFICATION |                                   |                                        |                   |                  | DIMENSIONS (in)              |                          |                   |                    |                         |                              |                          |                             | PACK QTY |
|--------------------|-----------------------------------|----------------------------------------|-------------------|------------------|------------------------------|--------------------------|-------------------|--------------------|-------------------------|------------------------------|--------------------------|-----------------------------|----------|
| Part Number        | Cable Size<br>(AWG/MCM/<br>kcmil) | Flex Cable Size<br>(AWG/MCM<br>/kcmil) | Hole Stud<br>Size | Die Index<br>No. | Internal<br>Diameter<br>(ID) | Overall<br>Length<br>(A) | Palm Width<br>(B) | Palm Length<br>(C) | Barrel<br>Length<br>(D) | Stud Hole<br>Distance<br>(E) | Palm<br>Thickness<br>(F) | Stud Hole<br>Spacing<br>(G) |          |
| 4CLF21458NW        | 4                                 | -                                      | 1/7               | 04               | 0.25                         | 2.36                     | 0.96              | 1.26               | 0.98                    | 0.28                         | 0.09                     | 0.63                        | 50       |
| 2CLF21434NW        | 2                                 | 4                                      | 1/4               | 02               | 0.31                         | 2.64                     | 0.75              | 1.38               | 1.1                     | 0.28                         | 0.11                     | 0.75                        | 25       |
| 2CLF21458NW        | 2                                 | 4                                      | 1/4               | 02               | 0.31                         | 2.52                     | 0.5               | 1.26               | 1.1                     | 0.28                         | 0.11                     | 0.63                        | 25       |
| 2CLF2141NW         | 2                                 | 4                                      | 1/4               | 02               | 0.31                         | 3.07                     | 0.5               | 1.81               | 1.1                     | 0.38                         | 0.11                     | 1.00                        | 25       |
| 1CLF21434NW        | 1                                 | 2                                      | 1/4               | 01               | 0.36                         | 2.68                     | 0.75              | 1.38               | 1.1                     | 0.28                         | 0.1                      | 0.75                        | 25       |
| 1CLF21458NW        | 1                                 | 2                                      | 1/4               | 01               | 0.36                         | 2.56                     | 0.5               | 1.26               | 1.1                     | 0.28                         | 0.1                      | 0.63                        | 25       |
| 1CLF2381NW         | 1                                 | 2                                      | 3/8               | 01               | 0.36                         | 3.11                     | 0.6               | 1.81               | 1.1                     | 0.38                         | 0.1                      | 1.00                        | 25       |
| 10CLF21458NW       | 1/0                               | 1                                      | 1/4               | 10               | 0.39                         | 2.66                     | 0.48              | 1.26               | 1.2                     | 0.28                         | 0.09                     | 0.63                        | 25       |
| 20CLF21458NW       | 2/0                               | 1/0                                    | 1/4               | 20               | 0.44                         | 2.87                     | 0.48              | 1.26               | 1.38                    | 0.28                         | 0.12                     | 0.63                        | 15       |
| 20CLF2141NW        | 2/0                               | 1/0                                    | 1/4               | 20               | 0.44                         | 3.43                     | 0.62              | 1.81               | 1.38                    | 0.38                         | 0.13                     | 1.00                        | 15       |
| 20CLF2381NW        | 2/0                               | 1/0                                    | 3/8               | 20               | 0.44                         | 3.43                     | 0.48              | 1.81               | 1.38                    | 0.38                         | 0.12                     | 1.00                        | 15       |
| 30CLF21458NW       | 3/0                               | 2/0                                    | 1/4               | 30               | 0.49                         | 2.95                     | 0.6               | 1.26               | 1.38                    | 0.28                         | 0.13                     | 0.63                        | 15       |
| 30CLF25161NW       | 3/0                               | 2/0                                    | 5/16              | 30               | 0.49                         | 3.5                      | 0.6               | 1.81               | 1.38                    | 0.32                         | 0.13                     | 1.00                        | 15       |
| 30CLF2381NW        | 3/0                               | 2/0                                    | 3/8               | 30               | 0.49                         | 3.5                      | 0.76              | 1.81               | 1.38                    | 0.38                         | 0.13                     | 1.00                        | 15       |
| 40CLF2381NW        | 4/0                               | 3/0                                    | 3/8               | 40               | 0.55                         | 3.54                     | 0.76              | 1.81               | 1.42                    | 0.38                         | 0.14                     | 1.00                        | 15       |
| 250CLF2381NW       | 250                               | 4/0                                    | 3/8               | 250              | 0.59                         | 3.78                     | 0.76              | 1.81               | 1.61                    | 0.38                         | 0.16                     | 1.00                        | 10       |
| 250CLF212134NW     | 250                               | 4/0                                    | 1/2               | 250              | 0.59                         | 4.96                     | 0.96              | 2.99               | 1.61                    | 0.62                         | 0.16                     | 1.75                        | 10       |
| 300CLF2381NW       | 300                               | 250 G,H                                | 3/8               | 300              | 0.66                         | 4.13                     | 0.52              | 1.81               | 1.97                    | 0.38                         | 0.13                     | 1.00                        | 10       |
| 350CLF2381NW       | 350                               | 250 G,H,I,K,M 262 DLO                  | 3/8               | 350              | 0.7                          | 4.21                     | 0.96              | 1.81               | 1.97                    | 0.38                         | 0.18                     | 1.00                        | 5        |
| 350CLF212134NW     | 350                               | 250 G,H,I,K,M 262 DLO                  | 1/2               | 350              | 0.7                          | 5.39                     | 0.96              | 2.99               | 1.97                    | 0.62                         | 0.18                     | 1.75                        | 5        |
| 400CLF2381NW       | 400                               | 300 G,H,I,K,M 313 DLO                  | 3/8               | 400              | 0.76                         | 4.29                     | 0.96              | 1.81               | 1.97                    | 0.38                         | 0.18                     | 1.00                        | 5        |
| 400CLF212134NW     | 400                               | 300 G,H,I,K,M 313 DLO                  | 1/2               | 400              | 0.76                         | 5.47                     | 0.96              | 2.99               | 1.97                    | 0.62                         | 0.18                     | 1.75                        | 5        |
| 500CLF2381NW       | 500                               | 350 G,H,I,K,M 373 DLO                  | 3/8               | 500              | 0.83                         | 4.57                     | 0.96              | 1.81               | 2.24                    | 0.38                         | 0.23                     | 1.00                        | 5        |
| 500CLF212134NW     | 500                               | 350 G,H,I,K,M 373 DLO                  | 1/2               | 500              | 0.83                         | 5.75                     | 0.76              | 2.99               | 2.24                    | 0.62                         | 0.23                     | 1.75                        | 5        |
| 600CLF212134NW     | 600                               | 400 G,H,I,K,M 444 DLO                  | 1/2               | 600              | 0.93                         | 5.79                     | 1.12              | 2.99               | 2.24                    | 0.62                         | 0.26                     | 1.75                        | 1        |
| 750CLF2381NW       | 750                               | 600 G,H,I 646 DLO                      | 3/8               | 750              | 1.03                         | 5.12                     | 1.12              | 1.81               | 2.64                    | 0.38                         | 0.26                     | 1.00                        | 1        |
| 750CLF212134NW     | 750                               | 600 G,H,I 646 DLO                      | 1/2               | 750              | 1.03                         | 6.3                      | 1.3               | 2.99               | 2.64                    | 0.62                         | 0.26                     | 1.75                        | 1        |
| 1000CLF212134NW    | 1000                              | 750 G,H,I 777 DLO                      | 1/2               | 1000             | 1.19                         | 6.81                     | 1.5               | 2.99               | 3.15                    | 0.62                         | 0.38                     | 1.75                        | 1        |