

CMP-MH060

Manual Hydraulic Crimping Tool - 60 kN / 6 ton



This lightweight manual hydraulic crimping tool is ideal for crimping cable lugs ranging from 6 mm² to 300 mm² (#8 AWG to 600 kcmil) and is compatible with CMP SBH & SBU crimping dies.

With its 350° rotating head for ease of use and a double-speed action for quick die advancement, it offers an excellent weight-to-capacity ratio. The built-in safety valve automatically bypasses the oil supply when maximum pressure is reached, ensuring safety during operation.

Full CMP die sets are available upon request—contact CMP Products for more information.

TECHNICAL DATA

ETIM Classification	EC000168
Force (kN)	60
Stroke Length (mm)	17
Cable Size Range (mm ²)	6 - 300
Cable Size Range (AWG/kcmil/MCM)	8 - 600
Length (mm) (Inch)	460 18.11
Weight (kg) (lb)	3.3 7.28
Container Type	Steel Case
Compatible Crimping Die	SBH, SBU
Operating Temperature Range (°C)	-10 to +60

Features

- Wide crimping range: Copper cables 6 mm² to 150 mm² - #8 AWG to 650 kcmil
- Very light head, excellent weight to capacity ratio
- Compatible with CMP SBH & SBU crimping dies
- 350° head rotation
- Double speed action: for fast die advancing speed
- Built-in safety valve will by-pass the oil supply when maximum pressure is reached
- Can be sold with full CMP die sets on request; contact CMP Products for more information

Ordering Information

Ordering Code	Die Set	Scope of Supply
CMP-MH060-B	-	Crimping tool - bare unit, hard plastic carrying case, carrying sling.
CMP-MH060-HS	SBH-S	Crimping tool - bare unit, hard plastic carrying case, carrying sling, crimping die set.
CMP-MH060-HH	SBH-H	
CMP-MH060-U	SBU	