

747

747 RECESSED STOPPER PLUG, GLOBALLY APPROVED, EXPLOSIVE ATMOSPHERE CABLE / CONDUIT ACCESSORY

- Provides means of blanking unused cable entries
- Temporary or permanent
- Tamper-proof (Type B) version available
- General purpose / industrial version available
- Nylon Ex e only version available (-20°C to +60°C)
- -60°C to +200°C (metallic versions)
- Globally marked, UKEX, IECEX, ATEX, cCSAus and UL (Metallic versions only)
- For use with threaded entry holes only - for stopper plugs suitable for use in clearance/through holes, please see 757 or 767
- Nylon stopper 717 / 717e to be used for sizes M20, M25, M32, 1/2", 3/4" and 1"

Type A




Type B




TECHNICAL CLASSIFICATION	
DESIGN SPECIFICATION	BS 6121:Part 1:1989
ENCLOSURE PROTECTION	IK10 to IEC 62262 (20 joules) Brass & Stainless Steel Only
INGRESS PROTECTION RATING	IP66
AVAILABLE MATERIALS	Brass, Electroless Nickel Plated Brass, Aluminium, Stainless Steel, Nylon
CONTINUOUS OPERATING TEMPERATURE	-60°C to +200°C (Metallic), -20°C to +60°C (Nylon)

GLOBAL PRODUCT CERTIFICATION			
ATEX CERTIFICATE	CML18ATEX1320X	IECEX CERTIFICATE	IECEX CML 18.0177X, IECEX SIM 15.0002X
UKEX CERTIFICATE	CML 21UKEX1238X	CODE OF PROTECTION	Ex db I Mb, Ex eb I Mb; Ex db IIC Gb, Ex ta IIC Da (Ex eb IIC Gb, Ex ta IIC Da only on Nylon version)
CODE OF PROTECTION	⊕ II 2G 1D Ex db IIC Gb, Ex eb IIC Gb, Ex ta IIC Da ⊕ I M2 Ex db I Mb, Ex eb I Mb (II 2G 1D Ex eb IIC Gb, Ex ta IIC Da only on Nylon version)	COMPLIANCE STANDARDS	IEC 60079-0, 1, 7, 31
COMPLIANCE STANDARDS	EN 60079-0, 1, 7, 31	UL CERTIFICATE	E214221 (Metallic versions only)
cCSAus CERTIFICATE	1055233 (Metallic versions only)	CODE OF PROTECTION	Class I, Groups A, B, C and D; IP66, 67, 68; Enclosure Type 4X; Class II Groups E, F and G; Class III Ex de II, Class I, Zone 1, AEx de II
CODE OF PROTECTION	Class I, Groups A, B, C and D; IP66, 67, 68; Enclosure Type 4X; Class II Groups E, F and G; Class III Ex de II, Class I, Zone 1, AEx de II	COMPLIANCE STANDARDS	UL 1203
COMPLIANCE STANDARDS	C22.2 No. 0, 0.5, 30.94, CSA C22.2 60079, 0, 1, 7, UL50, UL1203, UL 60079-0, 1, 7	UKrSEPRO CERTIFICATE	CLL 19.0372X
EAC CERTIFICATE	RU C-GB, A, D07.B.02500/20	CCOE / PESO (INDIA) CERTIFICATE	P444949
RETIE APPROVAL NUMBER	03866	INMETRO APPROVAL	TUV 12.1333X
CCC CERTIFICATE	2020322313001727	ECAS CERTIFICATE	20-02-05266
KCS KOSHA CERTIFICATE	14-GA4BO-0248X	SANS	IA MS-XPL21804 21.0006X
MARINE APPROVALS	LRS: 01/00173 DNV: TAE000000Y ABS: 17-LD-1619350-PDA, BV: 43180		

747 Type A Non tamper-proof



747 Type B Tamper-proof



HOW TO ORDER

e.g. 747 - D - A - M - 3 - 1

= Dual certified Ex d & Ex e - Type A - M25 - Aluminium

For Tamper-Proof Type B Stopper Plugs please substitute the letter A with the letter B in the ordering reference list opposite.

Other thread variations are available on request. For further information on ordering please refer to the Ordering Accessories page.

DESCRIPTION	ALLEN KEY RECESS	METALLIC			NON-METALLIC	
		Ex 'd'	Ex 'e'	INDUSTRIAL	Ex 'e'	INDUSTRIAL
747 RECESSED NON-TAMPER PROOF TYPE 'A'	✓	✓	✓	✓	✓	✓
747 RECESSED TAMPER-PROOF TYPE 'B'	✓	✓	✓	✓	✓	✓
757 HEXAGON HEAD	x	✓	✓	✓	✓	✓
757 HEXAGON HEAD C/W O-RING SEAL	x	✓	✓	✓	✓	✓
767 DOME HEAD	✓	✓	✓	✓	✓	✓
767 DOME HEAD C/W O-RING SEAL	✓	✓	✓	✓	✓	✓
717 UNIVERSAL	✓	x	x	x	✓	✓

PRODUCT SELECTION TABLE			
ORDERING REFERENCE	THREAD SIZE	MINIMUM THREAD LENGTH	ALLEN KEY SIZE A/F
747DAM1	M16 X 1.5	15.0	M8
747DAM2	M20 X 1.5	15.0	M10
747DAM3	M25 X 1.5	15.0	M10
747DAM4	M32 X 1.5	15.0	M10
747DAM5	M40 X 1.5	15.0	M10
747DAM6	M50 X 1.5	15.0	M10
747DAM7	M63 X 1.5	15.0	M14
747DAM8	M75 X 1.5	15.0	M14
747DAM9	M90 X 2.0	24.0	M14
747DAM10	M100 x 2.0	24.0	M14

All dimensions shown are in millimetres unless otherwise stated

If a nylon stopper is required for sizes M20, M25, M32, 1/2", 3/4" and 1" please order 717 (see datasheet TDS811) or 717e (TDS823).