


E1W

E1W DOUBLE SEAL INDUSTRIAL CABLE GLAND


FOR ALL TYPES OF STEEL & ALUMINIUM WIRE ARMoured CABLES

- Metal-to-metal armour clamping
- Direct and remote installation
- Permanently crimped, low impedance earth termination
- Secure against self-loosening
- Displacement type inner seal
- Controlled outer load retention seal
- Unique OSTG prevents overtightening
- Deluge protection option
- -60°C to +130°C
- Superior EMC performance



TECHNICAL CLASSIFICATION	
DESIGN SPECIFICATION	BS 6121-Part 1:1989, IEC 62444, EN 62444
MECHANICAL CLASSIFICATION*	Impact = Level 8, Cable Anchorage = Class D
ENCLOSURE PROTECTION	IK10 to IEC 62262 (20 joules) Brass and Stainless Steel only
ELECTRICAL CLASSIFICATIONS*	Category B
INGRESS PROTECTION RATING**	IP66 as standard (IP67, IP68*** available upon request)
CABLE GLAND MATERIAL	Brass, Electroless Nickel Plated Brass, Aluminium
CABLE TYPE	Single Wire Armour (SWA), Aluminium Wire Armour (AWA)
SEAL MATERIAL	CMP Thermoset Rubber
SEALING TECHNIQUE	CMP Inner Displacement Seal and Outer Load Retention Seal
SEALING AREA(S)	Cable Inner Bedding and Outer Cable Sheath
ARMOUR CLAMPING	Detachable Armour Cone and AnyWay Universal Clamping Ring

GLOBAL PRODUCT CERTIFICATION	
GOST R CERTIFICATE	04ИДЮ101.ГВ.С02492
MARINE APPROVALS	LRS: 01/00171, ABS: 16-LD1472056-PDA



* Mechanical and Electrical Classifications applied as per IEC 62444 and EN 62444 ** When CMP installation accessories are used. Refer to www.cmp-products.com for further information.
 *** IP68 tested to a minimum depth of 30 metres for 12 hours, alternative depths / durations can be provided upon request

COMBINED ORDERING REFERENCE (*BRASS METRIC)			AVAILABLE ENTRY THREADS 'C' (ALTERNATIVE METRIC THREAD LENGTHS AVAILABLE)					CABLE BEDDING DIAMETER 'A'		OVERALL CABLE DIAMETER 'B'		ARMOUR RANGE		ACROSS FLATS 'D'		ACROSS CORNERS 'D'		PROTRUSION LENGTH 'F'	SHROUD	CABLE GLAND WEIGHT (kg)
			STANDARD		OPTION															
SIZE	TYPE	ORDERING SUFFIX	METRIC	THREAD LENGTH (METRIC) 'E'	NPT	THREAD LENGTH (NPT) 'E'	NPT	MIN	MAX	MIN	MAX	MIN	MAX	MAX	MAX	MAX	MAX			
16	E1W	1RA	M16	10.0	½"	19.9	¾"	3.1	8.6	6.1	13.1	0.8	1.25	24.0	26.4	72.5	PVC04	0.163		
20S16	E1W	1RA	M20	10.0	½"	19.9	¾"	3.1	8.6	6.1	13.1	0.8	1.25	24.0	26.4	72.5	PVC04	0.163		
20S	E1W	1RA	M20	10.0	½"	19.9	¾"	6.1	11.6	9.5	15.9	0.8	1.25	24.0	26.4	70.0	PVC04	0.150		
20	E1W	1RA	M20	10.0	½"	19.9	¾"	6.5	13.9	12.5	20.9	0.8	1.25	30.5	33.6	73.0	PVC06	0.210		
25S	E1W	1RA	M25	10.0	¾"	20.2	1"	11.1	19.9	14.0	22.0	1.25	1.6	37.5	41.3	89.0	PVC09	0.330		
25	E1W	1RA	M25	10.0	¾"	20.2	1"	11.1	19.9	18.2	26.2	1.25	1.6	37.5	41.3	89.0	PVC09	0.330		
32	E1W	1RA	M32	10.0	1"	25.0	1 ¼"	17.0	26.2	23.7	33.9	1.6	2.0	46.0	50.6	86.0	PVC11	0.430		
40	E1W	1RA	M40	15.0	1 ¼"	25.6	1 ½"	22.0	32.1	27.9	40.4	1.6	2.0	55.0	60.5	90.0	PVC15	0.620		
50S	E1W	1RA	M50	15.0	1 ½"	26.1	2"	29.5	38.1	35.2	46.7	2.0	2.5	60.0	66.0	91.0	PVC18	0.750		
50	E1W	1RA	M50	15.0	2"	26.9	2 ½"	35.6	44.0	40.4	53.0	2.0	2.5	70.1	77.1	95.0	PVC21	0.950		
63S	E1W	1RA	M63	15.0	2"	26.9	2 ½"	40.1	49.9	45.6	59.4	2.0	2.5	75.0	82.5	102.0	PVC23	1.340		
63	E1W	1RA	M63	15.0	2 ½"	39.9	3"	47.2	55.9	54.6	65.8	2.0	2.5	80.0	88.0	104.0	PVC25	1.340		
75S	E1W	1RA	M75	15.0	2 ½"	39.9	3"	52.8	61.9	59.0	72.0	2.0	2.5	90.0	99.0	115.0	PVC28	2.110		
75	E1W	1RA	M75	15.0	3"	41.5	3 ½"	59.1	67.9	66.7	78.4	2.5	3.0	100.0	110.0	117.0	PVC30	2.420		
90	E1W	1RA	M90	24.0	3 ½"	42.8	4"	66.6	78.6	76.2	90.3	3.15	4.0	114.3	125.4	147.0	PVC32	4.210		
100	E1W	1RA	M100	24.0	3 ½"	44.0	4"	76.0	90.9	86.1	101.4	3.15	4.0	123.0	135.3	140.0	LSF33	4.450		
115	E1W	1RA	M115	24.0	4"	44.0	5"	86.0	97.9	101.5	110.2	3.15	4.0	133.4	146.7	162.0	LSF34	6.190		
130	E1W	1RA	M130	24.0	5"	46.8	6"	97.0	114.9	110.2	123.2	3.15	4.0	152.4	167.6	174.0	LSF35	8.340		

* Note : For material options please add the following suffix to change the ordering reference ; Brass (no suffix required), Nickel Plated Brass "5", Copper Free Aluminium "1"
 For NPT options please add the following digits to the material suffix ; ½" = 31, ¾" = 32, 1" = 33, 1 ¼" = 34, 1 ½" = 35, 2" = 36, 2 ½" = 37, 3" = 38, 3 ½" = 39, 4" = 310 (Brass requires prefix "0")

Examples: 32E1W1RA534 = Nickel Plated Brass 1 ¼" NPT, 50SE1W1RA035 = Brass 1 ½" NPT, 20E1W1RA5 = Nickel Plated Brass M20

Dimensions are displayed in millimetres unless otherwise stated